



sCELL-EF

LTE Enterprise Femtocell

2 x 2 MIMO

2 x 125mw

64 Concurrent Users


128 RRC Connected Users

The sCELL-EF from BTI Wireless is an enterprise-level 4G integrated Femto applying LTE technology. The product connects to the backbone network through wired backhaul and provides LTE access for terminals. It supports the transmission of voice and data with indoor wireless broadband coverage.

KEY FEATURES

- Integrated design of baseband and radio head
- Based on 3GPP LTE technology with high-speed data services
- Supports 5 MHz, 10 MHz, 15 MHz, 20 MHz bandwidth
- Convenient networking, plug and play solution, easy and flexible deployment
- External high-gain antenna for various usage scenarios
- Built-in DHCP server, DNS client and NAT functions, powerful high-speed routing capabilities
- Plentiful security service provides real-time protection, to prevent potential security risks and illegal intrusion
- Web-based management, convenient and intuitive
- Complete network management function
- Humanized indicator light, easy to observe and manage equipment status
- IP20 protection level

APPEARANCE



INTERFACE SPECIFICATIONS

| INTERFACE NAME | QUANTITY | INTERFACE TYPE | INTERFACE DEFINITION |
|----------------|----------|----------------|---|
| WAN/ PoE | 1 | RJ45 | Data return and PoE+ power supply interface |
| LAN | 1 | RJ45 | Local debugging interface |
| USIM | 1 | | USIM card slot |
| SFP (Optional) | 1 | SFP | Data transmit back to optical interface |
| DC 12V | 1 | DC Socket | 12V DC power supply interface |
| RST | 1 | | Manual reset device button |
| GPS | 1 | SMA | GPS antenna interface |

HARDWARE SPECIFICATIONS

| | |
|--------------------------|---------|
| Work Style | LTE FDD |
| Working Frequency | B1/3 |

| | |
|----------------------------|---|
| Working Bandwidth | 5 MHz/ 10 MHz/ 15 MHz/ 20 MHz |
| Transmit Power | 2 x 21 dBm |
| Synchronization | Supports GPS, IEEE 1588 V2, IEEE 1588 ACR and air interface synchronization |
| Backhaul Method | RJ-45 ethernet port (1GE), SFP optical port |
| MIMO | 2 x 2 |
| Equipment Size | 220 mm x 220 mm x 39 mm 8.66 in x 8.66 in x 1.54 in |
| Installation Method | Wall hanging, ceiling, desktop |
| Power Consumption | < 15W |
| Power Supply | 220V AC to 12V DC power adapter, PoE+ |
| Weight | < 0.65 kg 1.43 lbs |
| Equipment Capacity | < 1.9 L |

SOFTWARE SPECIFICATIONS

| | |
|-------------------------------------|---|
| Technical Standard | 3GPP Release 12 |
| Peak Rate (20 MHz Bandwidth) | DL: 150 Mbps (64QAM)/ UL: 75 Mbps (64QAM) |
| Operational Capacity | Supports 64 concurrent users, 128 RRC connected users |
| Scheduling Method | 3GPP standard QCI |
| Modulation | Downlink: QPSK, 16QAM, 64QAM Uplink: QPSK, 16QAM, 64QAM |
| Voice Solution | VoLTE |
| SON | Supports automatic configuration, ANR and PCI conflict detection |
| Network Management Interface | Supports TR069 interface protocol |
| MTBF | < 150,000 hours |
| MTTR | < 1 hour |
| O&M | <ul style="list-style-type: none"> Remote/local maintenance, based on SSH protocol Online status management Performance statistics Fault management Configuration management Local or remote software upgrade and loading Supports log Connectivity diagnosis Self-start and self-configuration deployment Alarm reporting Supports KPI reporting User information tracking |

ENVIRONMENTAL SPECIFICATIONS

| | |
|------------------------------|-----------------------------------|
| Operating Temperature | -5 °C ~ +45 °C +23 °F ~ +113 °F |
| Humidity | 10% ~ 95% |

Contact Us

www.btiwireless.comsales@btiwireless.com